



Selling Points

Engine

MITSUBISHI 4M50,4-cylinder, 4-stroke water-cooled, electronic injection, common rail, with turbocharge

Hydraulic system

 Swash-plate type duplex variable displacement piston pump, Kawasaki Brand (a group company of Japanese INLINE), Model:K3V112; max. flow rate 2* 234 l/min

Undercarriage

 Crawler carrier in box structure,49 pieces of track pad on each side, 9pieces of track roller each side, and 2 pieces of track carrier roller each side

Slewing System


- Full hydraulic drive
- Slewing motor, swash-plate type piston motor
- Double planetary gear reduce

Machine dimensions(mm)

Standard

E

G




	SY215CLR
A Overall length(in transportation state)	12,357
B Overall width(in transportation state)	3,180
C Overall height(in transportation state	3,265
D Upper width	2,875
E Overall height to cab top	3,075
F Width of Standard Track Shoe	800
G Track gauge	2,380
H Minimum ground clearance	470
I Slewing radius of tail	2,900
J Length of Track on Ground	3,640
K Crawler length	4,446
Width of undercarriage	2,980
Grouser height	26
Counterweight ground clearance	1,130
Standard Boom Length	8,500
Standard Arm Length	6,020

Working Performance

Standard

	SY215CLR
Working weight	24,150 kg
Bucket capacity	0.5 m³
Engine power	118kw/2000rpm
Width of track pad	800 mm
Digging Force of Bucket	115.8kN
Digging Force of Stick	62.1kN

Working Scope Standard



	SY215CLR
A Max. Digging Height	11,265 mm
B Max. Dumping Height	9,275 mm
C Max. Digging Depth	11,970 mm
D Max. Digging Distance	15,030 mm
E Min. Slewing Radius	5,765 mm
F Maximum height at minimum slewing radius	9 615 mm

Shanghai Sany Heavy Machinery(LTD)

Address: Sany Heavy Machinery Industrial Park, Pingan town, Fengxian District, Shanghai, China Zip Code:201413 Service Hotline:4008-28-2318 Inquiring and Complaint Number:4008-87-9318 Web:http://www.sany.com.cn

