



Strong Power Value Leader

Brand new change

Quality changes the world

Selling Points

- Engine
- MITSUBISHI 4M50,4-cylinder, 4-stroke water-cooled, direct injection, turbocharged & inter-cooled
- Euro 3

Slewing System

- Full hydraulic drive
- Slewing motor, swash-plate type piston motor Double planetary gear reducer


Hydraulic system


 Swash-plate type duplex variable displacement piston pump, Hengli Brand, Model: V90N130VRE1/ BJ1KOGM-T2G3; Max. flow rate 2* 260 l/min

Drive and Brake System

- Self-propelled, full hydraulic drive
- Traveling motor, swash-plate type piston motor
- Planetary gear reducer

Dimensions Standard






	SY285ME
A Overall length(in transportation state)	11,944
B Overall width(in transportation state)	4,595
C Overall height(in transportation state)	3,853
D Slewing radius of tail	3,345
E Counterweight ground clearance	2,040
F Min. ground clearance	1,255
G Length of Track on Ground	3,600
H Crawler length	8,135
J Track gauge	2,900
K Width of track pad	1,300
L Grouser height	1,815
M Overall height to cab top	4,020
N Width of slewing table	2,875
Standard Boom Length	6,900
Standard Arm Length	4,000

Working Performance SY285ME Working weight 27,500kg Bucket capacity 0.8 m³ Engine power 118kw/2000rpm Width of track pad 1,300mm Digging Force of Bucket 109.4kN Digging Force of Stick 89.7

Working Scope Standard



	SY285ME
A Max. Digging Height	10,595 mm
B Max. Dumping Height	8,250 mm
C Max. Digging Depth	8,010 mm
D Max. Digging Distance	11,950 mm
E Min. Slewing Radius	4,947 mm
F Maximum height at minimum slewing radius	9.102 mm

A SANY Heavy Machinery Co., Ltd.

SANY Industrial Park, Dongcheng Avenue, Kunshan Economic & Technological Development Zone, Jiangsu Province Post code: 215300

After-sales service hotline: 4008-28-2318 Consulting & complaint hotline: 4008-87-9318 Website: http://www.sanygroup.com

