

# 130-BARREL FRACTURING BLENDER TRUCK

## Product advantages

- Power is from engines on both chassis and platform and is sufficient;
- High precision guided wave radar level gauge, and stable liquid level of mixing tank with reliable control;
- Intake and outlet use the imported centrifugal pump, high-precision imported electromagnetic flowmeter, high-precision liquid-adding mass flowmeter and selected environment-friendly density meter which make data reliable;
- Double-screen construction operation system ensures the humanization and intellectualization of the operation process and the real-time automatic drawing of construction curve;
- The operating system is easy to operate, and can realize the functions of real-time monitoring, manual-automatic switching control and parameters setting and calibration of the blender truck;
- Low-pressure manifold material, densitometer, union joint can be selected and customized according to customer's needs.

Sufficient  
Power

Stable Liquid  
Level

Reliable  
Data

Intelligent  
Control

Simple  
Operation



**SANY PETROLEUM INTELLIGENT EQUIPMENT CO., LTD.**



Main performance indexes of blender truck with capacity of 130 barrels

Parameters	Values
Rated clear water displacement	20(130) m³/min(bbl)
Maximum discharge pressure	0.5Mpa
Maximum sand transportation volume	360 m³/h(11500kg/min)
Displacement of liquid adding system	15, 68, 63, 136/L/min
Displacement of dry adding system	10, 50L/min
Mixed tank volume	1.5 m³
Installed power	881(565+316)KW
Truck outside dimension (L×W×H)	12850×2550×3950 mm
Turning diameter	29m
Total equipment weight	33000kg

Main configuration of blender truck with capacity of 130 barrels

Names of Elements	Standard configuration	Remarks
Truck chassis	SANY SYM5550T1E	-
Superstructure engine	TAD1643VE-B 565kW Tier3 Volvo PTO	-
Suction centrifugal pump	12"×12"×14 7/8 "	Imported
Discharge centrifugal pump	14"×12"×22"	Imported
Flowmeter	10" electromagnetic flowmeter	-
Densimeter	Environmental-friendly radio densitometer	Provided for selection
Liquid adding system	CAT311, CAT1541, SPX18, SPX30	-
Dry adding system	BSL-P1-10L, BSL-P1-50L	-
Union on left side	6 1/8"-3ACME-2G	Optional coarse thread
Union on right side	6 1/8"-3ACME-2G	Optional coarse thread
Low pressure manifold	Carbon steel/stainless steel	Provided for selection

SANY PETROLEUM INTELLIGENT EQUIPMENT CO., LTD.

SANY Industrial Park, Liliu Road, Caozhuang Village, Nankou Town, Changping District, Beijing, China  
SANY Industrial Park, Xingsha, Changsha City, China  
Tel.: 010-60766720 0731-84031220  
Web: [www.sanygroup.com](http://www.sanygroup.com)

With the continuous updating of technologies, the technical parameters may change without further notice. The machine on the picture may include the auxiliary equipment. The picture manual is for reference only, and the actual product shall prevail. The copyright is reserved by the Sany Heavy Industry. Without the written approval of Sany Heavy Industry, any part of this catalog shall not be copied or duplicated for any purposes.

