





High reliability

With high-strength and low-stress frame, the integral stress level is 50% lower than that of similar products.



High security

Hydraulic steering, emergency steering Emergency action is available after losing power accidentally.



High comfort

Front suspension adopts hydro-pneumatic suspension instead of traditional leaf spring to make driving more comfortable.



High attendance rate

Low failure rate and high attendance rate greatly improve the profit capability and reduce the maintenance cost.



Smart electronic control system

Smart network, smart protection, preventive maintenance, procedure remote upgrade.

Main technical parameters

Items	Parameters
Body capacity (m³)	Struck 33 / Heaped 35
Gearbox	7DS200
Engine power (kW/ rpm)	338/2,100
Axle (t)	25+35+35
Steering form	Full hydraulic steering + emergency steering
Suspension structure	Front hydro-pneumatic suspension + rear leaf spring suspension
Frame structure	Riveted integral frame
Displacement (L)	11.6
Max. gradeability (%)	30
Min. ground clearance (mm)	325
Min. turning radius (mm)	11,000

Weight parameters

Weights	kg	lb
Net weight	30,000	66,080
Rated payload	60,000	132,160
Max. gross weight	90,000	198,240

* The maximum gross vehicle weight includes alternative devices, all accessories and load, etc.

Overall dimensions

Overall dimensions	Value
Length (mm)	8,967
Width (mm)	3,468
Height (mm)	4,308

SANY HEAVY EQUIPMENT CO., LTD

Address: 16 Kaifa Road, Economic & Technological Development Zone Shenyang Liaoning Province, P.R.China.

Postal Code: 110027

Official Website: www.sanvglobal.com Sales Hotline | Tel: 0086-24 8931 8365

Customer Service Hotline | Tel: 0086-400 8808 318

Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice. The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.

Engine

- Model: Weichai WP12G460E310
- Rated power rate: 338kW/2100rpm
- Maximum torque : 2000N.m
- Engine emission conforms to GB20891-2014 standard.

Axle

- Heavy-load and full-floating semiaxle has strong carrying capacity.
- Enhanced main retarder and wheel side reducer have double- stage driving and larger driving force.
- High-strength cast steel axle housing, reliable and durable.

Steering system

- Full hydraulic steering, convenient, comfortable, reliable.
- Emergency steering provides backup steering force when losing steering force.

Dumping system

 ø196 lifting cylinder, the lifting process of single front cylinder is stable and reliable.

I Cab

- Full-frame structure ensures safety of drivers.
- Extra large front windshield ensures wider driving vision.



 Tire model: 14.00R25 (select appropriate patterns according to working conditions)

Suspension

- Front suspension: non-independent hydropneumatic spring suspension with hydro-pneumatic (nitrogen) suspension cylinder with the characteristic of variable damping. It has large energy storage unit and variable stiffness to absorb the impact on the road.
- Rear suspension: equipped enhanced leaf spring, maintenance-free balance shaft and tie rod.
- Balance shaft: ø130 mm maintenance -free balance

∠ Bodv

- Container skeleton adopts pulling-through structure with higher strength.
- Main steel plate adopts high strength wearing plate with longer service life.
- Volume: struck: 31 m³; heaped: 35 m³

Optional configurations

Part	Options
Tail-rising hopper	Load and unload large-diameter materials
Centralized lubrication system	Fill grease automatically
Automatic fire extinguishing system	Automatic fire extinguishing in engine compartment
Air suspension seat	Improve driving comfort
Vacuum tire	Tubeless tire
Braking sprinkler	Spray on the rake drum to lower its temperature
Hydrodynamic retarder	Assist braking, providing force of retarder
Extended brim	The brim covers the cab

