



SANY ROADHEADER

EBZ318H



Technical data

Main parameter	Product model	EBZ318H
Gross weight (t)		120
Overall length (m)		13.1m
Width of mouldboard (m)		3.8/3.4
Width across tracks (m)		2.93
Overall height (m)		Body height 2.2/Highest point with horizontally arranged cutting head 2.7
Dimension of maximum undetectable part (m)		Body 3.30×1.45×1.67; Front chute 3.30×0.78×0.60; Motor box 2.30×1.83×1.14
Weight of maximum undetectable part (t)		11.5
Positioning cutting height (m)		Rectangular roadway 3.1 ~ 5.7; Arched roadway 3.6 ~ 5.7
Positioning heading height (m)		4 ~ 6.81
Max/economic unidirectional pressure resistance of rock (MPa)		100/80
Power of cutting motor (kW)		318
Rotating speed of cutting head (r/min)		31.8
Oil pump motor power (kW)		200
Ground pressure (MPa)		0.165
Dinting depth (mm)		220
Power supply voltage (V)		1140
Grade ability (°)		±18

Specifications

Hydraulic System

- The load-sensitive hydraulic system features low energy consumption and flexible and user-friendly operation.
- The multi-way valve cooperates to realize stepless speed regulation, with high efficiency and stability.

Shipping System

- The shovel adopts an open-type design of front driven wheel to improve the material receiving capacity; The scraper conveyor channel adopts smooth design to effectively solve the transportation jam. The transportation system adopts 14+6 composite wear-resistant plate. The wear-resistant life is increased by 3-5 times.

Overall Performance

- The equipment is heavy, its center of gravity is low, its layout is reasonable, and its overall performance is stable and reliable. It is suitable for drive in coal rock, semi-coal rock and rock roadway.

Cutting System

- The independently developed cutting head design software can automatically determine the pick arrangement scheme, stress analysis, and cutting effect simulation to achieve the maximum cutting efficiency and the minimum pick consumption. Alloy shot pick, the pick consumption is reduced by more than 30%.

SANY HEAVY EQUIPMENT CO., LTD

Address: 16 Kaifa Road, Economic & Technological Development Zone

Shenyang Liaoning Province, P.R.China.

Postal Code: 110027

Official Website: www.sanyglobal.com

Sales Hotline | Tel: 0086-24 8931 8365 Customer Service Hotline | Tel: 0086-400 8808 318

Reminder:

Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice. The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail. Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.



Follow our WeChat official account to learn more.